

Nut

Outdoor Projectors



Life is **Light**



Nut



Structural features

Installation: floor, wall and pole

Luminaire housing: die-cast aluminium

Louver: tempered glass

Reflector: super-pure oxidised and polished aluminium

Optical components: spot, superspot, medium, flood, road, symmetrical and asymmetrical

Light sources: metal-halide discharge lamps

Accessories: base and wall/pole fixing supports, wall-washer shields, anti-glare shields,

directional louvers, anti-vandalism protection grid

Standard finishing: grey, anthracite

Protection class: IP65

Insulation class: II

Power supply: 230V -50Hz







Life is Light

Nut

Light sources

DISCHARGE LAMPS

	MT (CDM-T) - G12	70W
	MT (CDM-T) - G12	150W
	MT (CDM-T) - G12	250W
	MD (CDM-TD) - RX7s	70W
	MD (CDM-TD) - RX7s	150W
	MD - Fc2	250W
	PGZ12	60W
	PGZ12	140W



Life is Light

Phoenix

Structural features

Installation: pole, wall, ground

Luminaire housing: die-cast aluminium

Louver: tempered glass

Reflector: super-pure oxidised and polished aluminium

Optical components: spot, flood, asymmetrical lamps.

Light sources: metal-halide discharge lamps

Accessories: bases for wall and ground mounting, pole-mounting support, wall-washers and anti-glare shields, anti-vandalism protection grid

Finishing: grey, anthracite

Protection class: IP65

Insulation class: I 

Power supply: 230V - 50Hz














Life is Light

Phoenix

Light sources

DISCHARGE LAMPS

	MD (CDM-TD) - RX7s	70W
	MD (CDM-TD) - RX7s	150W
	MD (CDM-TD) - RX7s	70W
	MD (CDM-TD) - RX7s	150W
	MD - Fc2	250W
	MD - Fc2	250W
	MT (CDM-T) - G12	70W
	MT (CDM-T) - G12	150W
	MT (CDM-T) - G12	70W
	MT (CDM-T) - G12	150W
	STH - PG12-1	100W



Life is Light

Dinamis

Structural features

Installation: wall or pole-mounted

Luminaire housing: die-cast aluminium

Reflectors: super-pure oxidised and polished aluminium

Louvers: tempered glass

Light sources: metal-halide discharge lamps, compact fluorescent lamps, mains voltage halogen lamps

Standard finishing: white, grey, anthracite

Protection class: IP65

Insulation class: II 

Power supply: 230V - 50Hz




Life is Light


Dinamis

Light sources



DISCHARGE LAMPS

	MD (CDM-TD) - R7s	70W
	MD (CDM-TD) - R7s	150W
	MD (CDM-TD) - R7s	70W
	MD (CDM-TD) - R7s	150W

HALOGEN LAMPS

	HDG - R7s	max 150W
	HDG - R7s	max 300W

FLUORESCENT LAMPS

	FSQH (TC-D) - G24q-3	2 x 26W
	FSMH (T/E) - GX24q-4	2 x 42W



Life is Light

Traccia



Structural features

Installation: recessed, wall-mounted, ceiling-mounted, suspended, high-bay

Luminaire housing: anodised extruded aluminium profile. Louver: tempered glass, thickness 8 mm (recessed type) and 5 mm (Light type)

Reflector: 99.9% super-pure oxidised and polished aluminium


Optical component: symmetrical and asymmetrical

Light sources: T5 linear fluorescent lamps

Accessories: recessed box, coloured filters (yellow, red, blue) and anti-glare shields, supports and brackets for wall-mounting, cables with base for high-bay installation. Finishing: anodised natural

Protection class: IP67


Protection rating against mechanical shocks: IK09

Insulation class: I 

Power supply: 230V - 50 Hz

Light sources

FLUORESCENT LAMPS

	FDH (T) - G5	14W
	FDH (T) - G5	21W
	FDH (T) - G5	28W
	FDH (T) - G5	35W



Life is Light

Iky



Structural features

Installation: wall or ceiling

Luminaire housing: die-cast aluminium

Ballast housing: die-cast aluminium

Louver: tempered glass or polycarbonate


Reflector: die-cast coated aluminium

Light sources: compact fluorescent lamps,
discharge lamps and mains voltage
incandescent lamps

Gaskets: silicone

Standard finishing: white, grey, anthracite


Protection class: IP65


Insulation class: I 

Power supply: 230V -50Hz

Light sources

COMPACT FLUORESCENT LAMPS

 FSQ (TC-D) - G24d-3 - G24q-3 2 x 26W

 FSMH (T/E) - GX24q-4 2 x 42W

DISCHARGE LAMPS

 MD - (CDM-TD) - RX7s 70W

MAINS VOLTAGE INCANDESCENT LAMPS

 IAA - E27 2 x 75W max



Life is Light

Sail



Structural features

Installation: high-bay, wall, pole

Luminaire housing: diamond draw and die-cast aluminium

Louver: tempered glass

Reflectors: super-pure oxidised and polished aluminium

Light sources: metal-halide discharge lamps

Accessories: wall/pole fixing supports, wall-washer louvers, anti-glare shields, directional louvers, anti-vandalism protection grid

Standard finishing: grey, anthracite



Protection class: IP65

Insulation class: II

Power supply: 230V - 50Hz

Light sources

DISCHARGE LAMPS

	MT (CDM-T) - G12	70W
	MT (CDM-T) - G12	150W
	STH - PG12 - 1	100W



Life is Light

Round HILL Square HILL



Structural features

Installation: in-ground recessed

Luminaire housing: die-cast aluminium and stainless steel outer ring

Louver: tempered glass, 10 mm and 15 mm thick

Optical components: fixed and adjustable, symmetrical, asymmetrical, light blade

Light sources: very low voltage halogen lamps, mains voltage lamps, discharge lamps, fluorescent lamps

Standard finishing: stainless steel


Protection class: IP67 - IP65


Insulation class: I  - II  - III 

Power supply: 230V - 50Hz - 12V


Light sources

DISCHARGE LAMPS

 MT (CDM-T) - PGJ5 20W


 MT (CDM-T) - G12 35W

VERY LOW VOLTAGE HALOGEN LAMPS (12V)


 HRGI - GU4 max 20W

HRGI - GU5.3 max 20W

MAINS VOLTAGE HALOGEN LAMPS

 HSGI - GZ10 max 35W

COMPACT FLUORESCENT LAMPS

 FSQ (TC-D) - G24d-2 18W

FLUORESCENT

 FB - GX53 6W

Life is Light